




Discover our range of **standard ZFG multimode fibers**:




Specifications

Operating wavelength	0.3 – 4.5 μm
Typical optical loss @ 2.5 μm	< 10 dB/km
Fresnel loss (backwards reflection)	4% per face (air)
Coating material	UV curable acrylate
Operating temperature	- 180 to 150 $^{\circ}\text{C}$

Standard fiber	Core/clad diameter	Numerical aperture	Short term bend radius	Long term bend radius	Price/m
ZFG MM (0.15) 90/150	90/150 μm	0.15	≥ 15 mm	≥ 45 mm	25 €
ZFG MM (0.20) 100/160	100/160 μm	0.20	≥ 15 mm	≥ 45 mm	50 €
ZFG MM (0.20) 200/260	200/260 μm	0.20	≥ 25 mm	≥ 75 mm	70 €
ZFG MM (0.20) 300/360	300/360 μm	0.20	≥ 35 mm	≥ 100 mm	140 €
ZFG MM (0.20) 400/460	400/460 μm	0.20	≥ 45 mm	≥ 120 mm	220 €
ZFG MM (0.20) 600/680	600/680 μm	0.20	≥ 70 mm	≥ 150 mm	480 €

All our fibers are available as **fiber patch cables** or **fiber bundles**
LVF proposes also **IR screened fibers** and **endcaps solutions**

Typical attenuation



CUSTOMIZE your own fiber



- Custom NA (from 0.12 to 0.30)
- Custom core/cladding size (up to 1000 μm core diameter)

